





N-TYPE MONO-CRYSTALLINE MODULE

MUL-10M-605M-144

MULTIFIT Linear Power Output Warranty Standard

12 12-year Product Warranty **30** 30-year Linear Power Warranty



n-type TOPCon 4.0

Novel upgrade, enhancing module efficiency



SMBB Design

Enhancing current collection, minimizing power loss



Better Temperature Coefficient

$\leq -0.29\%/^{\circ}\text{C}$, adapting for high temperature



Non-destructive Cutting

Improved cell bending strength, ensuring mechanical performance



- IEC 61215, IEC 61730
- ISO 9001:2015:ISO Quality Management System
- ISO 14001:2015:ISO Environment Management System
- ISO 45001:Occupational Health and Safety

585~605W

POWER RANGE

0~+3%


POWER SORTING

23.4%MAX MODULE
EFFICIENCY**≤ 1.0%**FIRST YEAR
POWER DEGRADATION**≤ 0.4%**YEAR 2-30
POWER DEGRADATION

Mechanical Specifications

Outer dimensions (L x W x H)	2278 x 1134 x 35 mm
Cell type	n-type mono-crystalline
No. of cells	144 (6*24)
Frame technology	Aluminum, silver anodized
Front glass thickness	3.2 mm
Cable length (Including connector)	Portrait: (+)350 mm, (-)250 mm; Customized length
Cable diameter (IEC/UL)	4 mm ² / 12 AWG
① Maximum mechanical test load	5400 Pa (front) / 2400 Pa (back)
Connector type (IEC/UL)	HCB40 (Standard) / MC4-EVO2A (Optional)
Module weight	26.9 kg
Packing unit	31 pcs / box
Weight of packing unit (for 40'HQ container)	885 kg
Modules per 40' HQ container	620 pcs (Subject to sales contract)

① Refer to Multifit crystalline installation manual or contact technical department.
Maximum Mechanical Test Load=1.5×Maximum Mechanical Design Load.



Electrical Specifications

STC: Irradiance 1000W/m², Cell Temperature 25° C, AM=1.5

Rated output (Pmpp / Wp)	585	590	595	600	605
Rated voltage (Vmpp / V)	43.18	43.34	43.51	43.68	43.85
Rated current (Impp / A)	13.55	13.61	13.67	13.74	13.80
Open circuit voltage (Voc / V)	52.03	52.22	52.42	52.62	52.81
Short circuit current (Isc / A)	14.20	14.27	14.33	14.39	14.46
Module efficiency	22.6%	22.8%	23.0%	23.2%	23.4%

Temperature Ratings (STC)

Temperature coefficient (Pmpp)	-0.29%/°C
Temperature coefficient (Isc)	+0.043%/°C
Temperature coefficient (Voc)	-0.25%/°C

Operating Parameters

No. of diodes	3
Junction box IP rating	IP 68
Max. series fuse rating	25 A
Max. system voltage (IEC/UL)	1500V _{DC}

Curve

